

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 23/06/2020 Revision date: 28/04/2021 Supersedes version of: 12/02/2021 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : EASYLINE EDGE 750ml Aerosol, ALL COLOURS - From 23.06.20

UFI : 7800-D0RN-W00U-DDRD

Product code : 47000-47009
Type of product : Paint
Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use.Industrial use

Industrial/Professional use spec : Industrial

For professional use only

1.2.2. Uses advised against

Restrictions on use : Acetone is listed as a reportable explosives precursor in Annex II of EU regulation

2019/1148

1.3. Details of the supplier of the safety data sheet

Manufacturer

ROCOL a division of ITW Ltd Rocol House Wakefield Rd, Swillington LS26 8BS Leeds - United Kingdom

T +44 (0)113 232 2600

customer.service@rocol.com - www.rocol.com

1.4. Emergency telephone number

Emergency number : +44 (0)113 232 2600

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

Signal word (CLP) : Danger

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P271 - Use only outdoors or in a well-ventilated area.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note U)	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128- 37	10 – 30	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
CALCIUM CARBONATE COMMERCIAL GRADE substance with national workplace exposure limit(s) (GB)	CAS-No.: 471-34-1 EC-No.: 207-439-9 REACH-no: Exempt	10 – 30	Not classified
o-xylene substance with a Community workplace exposure limit (Note C)	CAS-No.: 95-47-6 EC-No.: 202-422-2 EC Index-No.: 601-022-00-9 REACH-no: 01-2119485822- 30	5 – 15	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
ACETONE substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1-METHOXY-2-PROPANOL substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 012119457435- 35-XXXX	2.4 – 10	Flam. Liq. 3, H226 STOT SE 3, H336

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
CARBON DIOXIDE AEROSOL PROPELLANT substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 124-38-9 EC-No.: 204-696-9 REACH-no: Exempt	1 – 2.4	Press. Gas (Comp.), H280

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard : Vapours may form explosive mixture with air. Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

28/04/2021 (Revision date) GB - en 3/12

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent

formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Store in a well-ventilated place. Keep cool. Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F. Store in a dry place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : $< 50 \, ^{\circ}\text{C}$

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

ACETONE (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetone	
IOEL TWA	1210 mg/m³	
IOEL TWA [ppm]	500 ppm	
Regulatory reference COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits		
Local name	Acetone	
WEL TWA (OEL TWA) [1]	1210 mg/m³	
WEL TWA (OEL TWA) [2]	500 ppm	
NEL STEL (OEL STEL) 3620 mg/m³		
WEL STEL (OEL STEL) [ppm]	1500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-METHOXY-2-PROPANOL (107-98-2)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	1-Methoxypropanol-2		
IOEL TWA	375 mg/m³		
IOEL TWA [ppm]	100 ppm		
IOEL STEL	568 mg/m³		
IOEL STEL [ppm]	150 ppm		
Notes	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	1-Methoxypropan-2-ol		
WEL TWA (OEL TWA) [1]	375 mg/m³		
WEL TWA (OEL TWA) [2]	100 ppm		
WEL STEL (OEL STEL)	560 mg/m³		
WEL STEL (OEL STEL) [ppm]	150 ppm		
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
CALCIUM CARBONATE COMMERCIAL GRADE (471-34-1)			
United Kingdom - Occupational Exposure Limits	United Kingdom - Occupational Exposure Limits		
Local name	Calcium carbonate (Limestone, Marble)		
WEL TWA (OEL TWA) [1]	10 mg/m³ total inhalable 4 mg/m³ respirable		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
dimethyl ether (115-10-6)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Dimethylether		
IOEL TWA	1920 mg/m³		
IOEL TWA [ppm]	1000 ppm		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits	United Kingdom - Occupational Exposure Limits		
Local name	Dimethyl ether		
WEL TWA (OEL TWA) [1]	766 mg/m³		
WEL TWA (OEL TWA) [2]	400 ppm		
WEL STEL (OEL STEL)	958 mg/m³		
WEL STEL (OEL STEL) [ppm]	500 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
CARBON DIOXIDE AEROSOL PROPELLANT	CARBON DIOXIDE AEROSOL PROPELLANT (124-38-9)		
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Carbon dioxide		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CARBON DIOXIDE AEROSOL PROPELLANT (124-38-9)		
IOEL TWA	9000 mg/m³	
IOEL TWA [ppm]	5000 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Carbon dioxide	
WEL TWA (OEL TWA) [1]	9150 mg/m³	
WEL TWA (OEL TWA) [2]	5000 ppm	
WEL STEL (OEL STEL)	27400 mg/m³	
WEL STEL (OEL STEL) [ppm]	15000 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
o-xylene (95-47-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	o-Xylene	
IOEL TWA	221 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m³	
IOEL STEL [ppm]	100 ppm	
Notes	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Hand protection:

Wear protective gloves.

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)			2 (< 1.5)	

8.2.2.3. Respiratory protection

Respiratory protection:

No respiratory protection needed under normal use conditions. In case of inadequate ventilation wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
Reusable half mask	Type P1, Type AX - Low-boiling (<65 °C) organic compounds	Mist formation, Protection for Liquid particles, Protection for Solid particles, Vapour protection, If conc. in air > exposure limit	

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Liquid.

Colour : Black. Blue. Green. Grey. Orange. red. white. Yellow. Odour : characteristic.

Odour threshold : No data available pH : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available Freezing point : No data available No data available

Boiling point : > 35 °C Flash point : < 23 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : Non flammable. : No data available Vapour pressure Relative vapour density at 20 °C : No data available No data available Relative density No data available Solubility Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available Explosive properties : No data available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Oxidising properties : No data available Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

CALCIUM CARBONATE COMMERCIAL GRADE (471-34-1)

LD50 oral rat 6450 mg/kg

dimethyl ether (115-10-6)

LC50 Inhalation - Rat [ppm] 164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 - 203000

Skin corrosion/irritation : Not classified

Additional information : Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified

Additional information : Based on available data, the classification criteria are not met

Respiratory or skin sensitisation : Not classified

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

STOT-single exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

ACETONE (67-64-1)

STOT-single exposure May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-METHOXY-2-PROPANOL (107-98-2)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	: Not classified	
Additional information	: Based on available data, the classification criteria are not met	
o-xylene (95-47-6)		
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)	
Aspiration hazard	: Not classified	
Additional information	: Based on available data, the classification criteria are not met	
EASYLINE EDGE 750ml Aerosol, ALL COLOURS - From 23.06.20		
Vaporizer	Aerosol	
Potential adverse human health effects and	: Based on available data, the classification criteria are not met	

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

symptoms

Hazardous to the aquatic environment, long-term

: Not classified

(chronic)

dimethyl ether (115-10-6)		
LC50 - Fish [1]	> 4.1 g/l Test organisms (species): Poecilia reticulata	
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna	
EC50 96h - Algae [1]	154.917 mg/l Test organisms (species): other:green algae	
o-xylene (95-47-6)		
LC50 - Fish [1]	7.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 72h - Algae [1]	4.7 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
NOEC (chronic)	1.17 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'	

12.2. Persistence and degradability

EASYLINE EDGE 750ml Aerosol, ALL COLOURS - From 23.06.20	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

EASYLINE EDGE 750ml Aerosol, ALL COLOURS - From 23.06.20	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

Additional information

Ecology - waste materials
European List of Waste (LoW) code

: Dispose in a safe manner in accordance with local/national regulations.

: Handle empty containers with care because residual vapours are flammable.

Avoid release to the environment.

: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous

substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
*	*	*	2	1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.