

Technical Data

FOODLUBE® PREMIER 1

Multipurpose, high performance food grade grease, EP1



Nonfood Compounds
Program Listed: H1
ISO 21469 Certified

Description

ROCOL® FOODLUBE Premier 1 is a soft, white, non-toxic grease containing PTFE for the effective lubrication and protection of ball, roller and plain bearings, slides and bushes particularly those operating in food, pharmaceutical and other clean environments.

FOODLUBE Premier 1 is an excellent all round NLGI No.1 grease offering excellent water wash off resistance and corrosion protection necessary for lubricants used in food, pharmaceutical and other clean environments.

Applications

- Ball Bearings
- Roller Bearings
- Plain Bearings
- Linear Bearings
- Slides
- Bushes
- Electric Motor Bearings
- Conveyors
- Bearings running at high speed

Approvals / Specifications

- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Manufactured from only FDA listed ingredients:
 - FDA Group 21 CFR 178.3570
- NSF H1 registered – 141084
- ISO 21469
- Halal certified
- Kosher certified
- Rocol unique TPM number – 43

Features & Benefits

- Offers an excellent wide temperature resistance of -30°C to +180°C
- DETEX - Cartridge has metal detectable plastic components (end caps) capable of detection by most metal detection equipment.
- Excellent EP performance with a 4-ball weld load of 315 kg.
- Highly resistant to water wash off and offers excellent corrosion protection.
- Excellent oxidation stability resulting in extended relubrication intervals and a reduction in lubricant usage.
- Excellent pumpability

Directions For Use

FOODLUBE Premier 1 can be applied manually, by grease gun, keg pump or by other methods suitable for an NLGI No. 1 grease.

FOODLUBE Premier 1 is compatible with other soap thickened greases. However, for best results the previous lubricant should be removed prior to application.

The storage temperature should be controlled between +1°C and +40°C.

Shelf life is 3 years from date of manufacture.

Further Information

For pack sizes, part codes and safety data sheets please visit www.rocol.com or get in touch with our customer service team who will be happy to help: customer.service@rocol.com

Technical Data

FOODLUBE® PREMIER 1

Multipurpose, high performance food grade grease, EP1



Nonfood Compounds
Program Listed: H1
ISO 21469 Certified

| Property | Test Method | Result |
|------------------------------|-------------------|------------------------------|
| Appearance | Visual | White tenacious grease |
| NLGI No. | IP 50 - ASTM D217 | 1 |
| Base Type | N/A | Polyalphaolefin |
| Base Fluid Viscosity at 40°C | IP71-ASTM D445 | 150cSt |
| dmN Rating | N/A | 450,000 |
| Thickener | N/A | Complex soap |
| Solids | N/A | PTFE/White, non-toxic solids |
| Temperature Range | N/A | -30°C to +180°C |
| 4-Ball Weld Load | IP239-ASTM D2596 | 315kg |
| SKF-ROF Bearing Life | N/A | 1390 hours |
| Corrosion Test-Emcor | IP 220 | 0:0 |
| Copper Corrosion Test | IP112-ASTM D130 | 1b |
| Water Washout Test | IP215-ASTM D1264 | <2% |

Values quoted above are typical and do not constitute a specification.

Issue 13 Date: 10/21

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740
E customer.service@rocol.com www.rocol.com
ROCOL House, Swillington, Leeds LS26 8BS

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

ROCOL® A division of **ITW** Ltd

